















Factory Add: No.255 Yindong South Rd., Yinzhou Economic Development Zone, Zhangi Town, Ningbo City, Zhejiang, China.

Email: sales@silanglighting.com Website: www.silanglighting.com Tel: (+86)-574-55003160

COMPANY PROFILE








30 +
Export country

\$30 million
Annual output



As a rising star of LED lighting industry, Ningbo SILANG Lighting is specialized in designing, manufacturing and developing LED lights. With years of lighting experience, we are dedicated to helping with the upgrading of indoor/outdoor lighting environment through our high-quality led downlights, security floodlights, smart lights and solar lights.

The company is located in Ningbo city, which is only a 30-minute drive from Ningbo Port. SILANG possesses strong advantages of both fast delivery and strong supply chain system.

SILANG's easy-to-use, innovative and reliable products are highly preferred by our loyal clients in Europe, Australia, New Zealand and now US markets. We offer a wide range of products and services, as well as multiple solutions to support the market growth you want.

SILANG embraces technical innovation and revolution. We believes that research and development investment is the key to brings new and innovative products to market with customer involvement.

Whatever your professional lighting needs, we'd love to help you with your current/next project





CERTIFICATION



OUR STRENGTH

- **Professional Lights with Competitive Price:**Well-designed products are developed and manufactured by our own lab and factory, together with our optimal self-made drivers. Our state-of-the-art equipment allows us to always provide quality LED lighting solutions with a reasonable price and flexible ordering quantities.
- Rigorous Quality Control: Focus on LED lighting for 10 years, the whole manufacturing process strictly follows the ISO9001 Quality Management System, meeting RCM, CE and ETL criteria. The QC department conducts IQC, inspection during the assembling, random inspection and even full inspection on request before shipping.
- Stable Delivery Time: Having 200+ skilled workers and 22 assembly lines, we've reached a product capacity of 600,000pcs per month, ensuring a fast delivery time. Meanwhile, locating in the port city, Ningbo, also means a great convenience for exportation.
 - **Strong R&D Capability:**SILANG embraces technical innovation and revolution. Thanks to our experienced and talented team members, SILANG's independent R&D department maintains a consistent pace of releasing 6+ new products each year. Besides, we offer deep customization service by requests from Australian, European and American markets.

Downlight











Security Light









Commercial Light



JBL Series

Coming Soon...

JCL Series



Work Light





DOWNLIGHT

DL-SG260-212D3 Code

Wattage 12W

2700K/3000K/4000K/5000K/6500K CCT(K)

Lumens 1050lm 100° Beam Angle Yes(Triac) Dimmable Material Nylon+Al+PC Height 30mm













Adjustable Spring

Fit in 5"/6" can housing



Easy to Install

Hook, push, and done





5"/6" 5CCT LED Can Light

SG Series			ccr (Rob) * ?	© CCT (669 💥 🎅
Code	DL-\$G260-212D3	DL-\$G360-212D3	DL-SG260-212D5	DL-\$G360-212D5
Wattage	12W	12W	12W	12W
Lumens	1050lm	960lm	1050lm	960lm
Beam Angle	100°	100°	100°	100°
Cutout	5-6inch	5-6inch	5-6inch	5-6inch
Height	30mm	28.5mm	30mm	28.5mm







SECURITY LIGHT

Photocell/Motion Sensor

Wide applications in various





Code WL-YDR-224P-D4

Wattage 24W

CCT(K) 3000K/4000K/6500K

Lumens 1900lm

Beam Angle 90°/head

Working Mode Auto/D2D/On time

Detection Brightness5-2000LuxDetection Angle120°Detection Distance12m maxMaterialPC



YDR series White Black

SL-YDR03-224D8

24W

D2D/On time

3CCT Outdoor Photosensitive LED Security Light

WL-YDR-224P-D5

24W

Auto/On time

120°/12m max

1900lm(BK)/2500lm(WH)

WL-YDR-224P-D4

24W

Auto/D2D/On time

120°/12m max







WL-YD2R-224P

24W

Auto/D2D/On time

180°/16m max



Wattage 40W

CCT(K) 3000K/4000K/6500K

Lumens 3800lm Beam Angle 90°/head

Working Mode Auto/D2D/On time

Detection Brightness5-2000LuxDetection Angle120°Detection Distance12m maxMaterialPC+Glass















YDS series White Black

3CCT Outdoor Photosensitive LED Security Light

YDS Series		*		1 tour
Code	WL-YDS03-240D8	WL-YDS-240P-D5	WL-YDS-240P-D4	WL-YDS-240P
Wattage	40W	40W	40W	40W
Lumens		3800lm(BK)/	/4400lm(WH)	
Working Mode	D2D/On time	Auto/On time	Auto/D2D/On time	Auto/D2D/On time
Detection Range	/	120°/12m max	120°/12m max	180°/16m max





Working Mode

Detection

Range

YDR Series

Code

Wattage

Lumens









Heat Dissipation Design





WL-YER-230P-D4 Code

Wattage 30W

CCT(K) 3000K/4000K/6500K

Lumens 2400lm 100°/head **Beam Angle Working Mode** Auto/D2D/On time

Detection Brightness 5-2000Lux **Detection Angle** 120° **Detection Distance** 12m max Material Aluminum+PC



YER series White Black

3CCT Round Photosensitive LED Security Light











Wattage

CCT(K) 3000K/4000K/6500K Lumens 4800lm-6000lm 100°/head **Beam Angle Working Mode** Auto/D2D/On time

Detection Brightness 5-2000Lux 120° **Detection Angle**

Detection Distance 12m max Material Al+PC+Glass









Photocell/Motion Sensor Wide applications in various







YES series white Black

US 3CCT Square Photosensitive LED Security Light

YES Series		*		
Code	WL-YES03-260D8	WL-YES-260P-D5	WL-YES-260P-D4	WL-YES-260P
Wattage	60W	60W	60W	60W
Lumens	4800lm-6000lm	4800lm-6000lm	4800lm-6000lm	4800lm-6000lm
Working Mode	D2D/On time	Auto/On time	Auto/D2D/On time	Auto/D2D/On time
Detection Range	/	120°/12m max	120°/12m max	180°/16m max









3 Wattage Turnable







CCT(K) 2700K/3000K/4000K/5000K/6500K

Lumens 2100lm max 110° **Beam Angle Dimmable** Yes Lenth 1.2m



Switch the brightness you







T8/5 series white

5CCT LED Batten Light

T8/5 series		Non
Code	SL-LT-JAL812	SL-LT-JAL512
Wattage	10W/15W/20W	10W/14W/18W
CCT(K)	2700K/3000K/4000K/5000K/6500K	3000K/4000K/6500K
Lumens	2100lm max	2000lm max
Beam Angle	110°	120°









CCT(K) 2700K/3000K/4000K/5000K/6500K

Lumens 2400lm/3600lm/4800lm

100° **Beam Angle** Dimmable No 1.2m Lenth Material PC+ABS+AL











2 Ways to Install

Suitable for various scenarios

JBL/JCL series white

5CCT LED Shop Light

JBL/JCL series	Non	New Year
Code	SL-LT-JBL4-240CT	SL-LT-JCL4-260CT
Wattage	20W/30W/40W	30W/45W/60W
CCT(K)	2700K/3000K/400	00K/5000K/6500K
Lumens	2400lm/3600lm/4800lm	3500lm/5400lm/7200lm
Material	PC+ABS+AL	PC+ABS









FLC36 Code

18W/27W/36W Wattage 3000K/4000K/6500K CCT(K)

Lumens 3800lm max 20VDC tool battery Input

Beam Angle 90°/head Material ABS















FLC series (Black)

3CCT Portable LED Floodlight


















- 5CCT in 1 with Multi-color available
- 13mm slim design can set up anywhere







Battery Light



Solar Light




Coming Soon...



BATTERY LIGHT

Code UB01 Wattage



Lumens 200lm 24° **Beam Angle Dimmable** Yes(Triac) ABS Material

3.7V 4000mAh **Battery USB Charging** Type-C

Endurance Time 4.5h











Color Changeable LED Reading Light















Motion/Wave Sensor





UB02-30

3000K-6000K

1.5W

120lm

Code

Wattage

CCT(K)

Lumens

UB05 Code Wattage 4W

CCT(K) 3000K/4000K/6000K

Lumens 320lm 0°-70° **Beam Angle Dimmable** Yes **Material** ABS

Battery USB Charging Type-C Endurance Time 4h









UB05 series White Black

3CCT Square Wall Light













Wireless Side-Emitting Under Cabinet Bar Light

UB02 series	New	Coning	Conning
Code	UB02-30	UB02-40	UB02-60
Wattage	1.5W	2W	3W
Lumens	120lm	160lm	240lm
Battery	3.7V 1500mAh	3.7V 2000mAh	3.7V 3000mAh
Duration Time	6h	6h	6h
Lenth(L)	30mm	40mm	60mm













BATTERY LIGHT





UB03-30

1.5W

120lm

3 hours

UB03-40

2W

3000-6500K

160lm

Yes

Type-C

4 hours

6 hours AUTO/OFF/ON TIME

120°

30s

0-4m <10cm

40cm

ABS+PC

3.7V 1500mAh 3.7V 2000mAh 3.7V 3000mAh

UB03-60

3W

240lm

5 hours

60cm



CCT(K) 3000K/4000K/6000K+RGB

Lumens 160-180lm 45°/110° **Beam Angle Dimmable** Yes **Material** ABS Diameter 85mm

3.7V 2000mAh **Battery** Type-C

USB Charging Endurance Time 6H










UBO6 series white

Wireless Connectable LED Cabinet Light







UB | Wireless Surface-Emitting Under Cabinet Bar Light **SPECIFICATIONS**

Code

Wattage

CCT(K)

Lumens

Battery

Dimmable

USB Charging

Charging Time

Endurance Time

Working Mode

Lenth(L)

Material

Detection Angle

Sensor Duration Time

Human Body Detection Distance

Hand Scan Detection Distance




2 Modes Optional Motion/ Handwave seneor activated

UB | Side-Emitting Connectable Under Cabinet Bar Light

SPECIFICATIONS

Code	UB04-30	UB04-40	UB04-60
Wattage	5W	6.5W	10W
CCT(K)		3000K-6500K	
Lumens	400lm	520lm	800lm
Dimmable		Yes	
Input	22	20-240V~50/60	Hz
Output	24V DC		
Working Mode	AUTO/NIG	HT/HAND WAV	'E/ON TIME
Detection Angle		120°	
Sensor Duration 1	ime	30s/60s/120s	
Human Body Det	ection Distance	• 0-4m	
Hand Scan Detec	ction Distance	<10cm	
Lenth(L)	30cm	40cm	60cm
Material		ABS+PC	





















OT-01A-4P3 Code Wattage

3000K/4000/6500K CCT(K)

180lm Lumens 30° **Beam Angle Dimmable** Yes ABS+PC Material 9mm Height **Solar Panel** 5.5VDC **Battery** 3.7V1800mAh **USB Charging** Type-C **Endurance Time** 2.5h

Detection Angle 120°



Adjustable Solar Panel Effencient solar powered & save energy





OT-01 series

30°/120° LED Solar Spike Light

OT series	Non	Non.	Non	Conning	Conning	Contro
Code	OT-01A-1D3	OT-01A-1R	OT-01A-4P3	OT-01B-1D3	OT-01B-1R	OT-01B-4P3
Wattage	1.2W	1.2W	4W	1.2W	1.2W	4W
Lumens	60-80lm	60-80lm	180lm	60-80lm	60-80lm	180lm
Illumination	240Lux/1m	240Lux/1m	750Lux/1m	240Lux/1m	240Lux/1m	750Lux
Beam Angle	30°	30°	30°	120°	120°	120°
Detection Angle	/	/	120°	/	/	120°
Endurance Time	8-10h	8-10h	2.5h	8-10h	8-10h	2.5h

OT | Colour Adjustable LED Solar Security Light

SPECIFICATION	S	
Code	OT-04	
Wattage	5W	
CCT(K)	3000K-6500K	
Lumens	520lm	
Dimmable	Yes	
Beam Angle	100°	
Solar Panel	5.5VDC	
Battery	3.7V 1800mAh	
Charging Time 8-1	0 hours by solar energy	
USB Charging	3.5 hours by Type-C	
Endurance Time	60 mins	
Worknig Mode	AUTO/D2D/ON TIME	
Detection Angle	120°	
Sensor Duration Tim	e 30s/60s/120s	
Detection Distance	6m max	
Material	ABS+PC	









OT | Colour Adjustable LED Solar Security Light


SPECIFICATION	NS SNC		
Code	OT-05		
Wattage	5W		
CCT(K)	3000K/4000K/6500K		
Lumens	400lm		
Dimmable	No		
Beam Angle	100°		
Solar Panel	5.5VDC		
Battery	3.7V 1800mAh		
Charging Time	8-10 hours by solar energy		
USB Charging	3.5 hours by Type-C		
Endurance Time	80 mins		
Detection Bright	ness 5-2000Lux		
Detection Angle	120°		
Sensor Duration	Time 3secs-8mins		
Detection Distan	ice 10m max		
Material	ABS+PC		

























Coming Soon...



with Brand New CommandX System Make group control more convenient

The coming interconnectable product family