







North America

COMPANY PROFILE







30 +
Export country

\$40 million
Annual output



Ningbo SILANG Lighting is a professional LED lighting manufacturer focused on designing, producing, and developing high-quality LED products. With years of experience, we help upgrade indoor and outdoor lighting with reliable downlights, floodlights, smart lights, and solar lights.

Based in Ningbo—just 30 minutes from Ningbo Port—we offer fast delivery and a strong supply chain. Our products are easy to use, innovative, and trusted by customers across Europe, Australia, New Zealand, and the US.

We continuously invest in R&D and work closely with our clients to bring new ideas to life. No matter what your project involves, we're here to provide lighting solutions that support your goals.





CERTIFICATION



OUR STRENGTH

- Competitive Pricing & Quality Products: We design and produce professional LED lights in our own lab and factory, using self-developed drivers and advanced equipment. This allows us to offer high-quality lighting at reasonable prices with flexible order quantities.
- Rigorous Quality Control: With over 10 years in LED lighting, we follow ISO9001 standards and meet CE, ETL, and RCM certifications. Our strict QC process includes incoming checks, assembly inspections, and pre-shipment full inspections upon request.
 - Stable & Fast Delivery: With 200+ skilled workers and 22 production lines, we output 600,000 pieces monthly. Being located just 30 minutes from Ningbo Port ensures smooth and efficient exports.
 - Strong R&D & Customization: Our dedicated R&D team launches 6+ new products each year. We also provide deep customization based on feedback from European, Australian, and American markets.
- Global Production Bases: We operate factories in both China and Vietnam, which ensures stable supply and competitive cost advantages.

Downlight





















Commercial Light





SLE260

Work Light







DOWNLIGHT

DL-SG260-212D3 Code

Wattage 12W

2700K/3000K/4000K/5000K/6500K CCT(K)

Lumen 1050lm 100° Beam Angle Yes(Triac) Dimmable Material Nylon+Al+PC Height 30mm











Adjustable Spring

Fit in 5"/6" can housing



Easy to Install

Hook, push, and done





SG series white Black

5"/6" 5CCT LED Can Light

SG Series			ccr (Rob) * ?	© CCT (600 ★ ♠
Code	DL-\$G260-212D3	DL-\$G360-212D3	DL-SG260-212D5	DL-\$G360-212D5
Wattage	12W	12W	12W	12W
Lumen	1050lm	960lm	1050lm	960lm
Beam Angle	100°	100°	100°	100°
Cutout	5-6inch	5-6inch	5-6inch	5-6inch
Height	30mm	28.5mm	30mm	28.5mm







SECURITY LIGHT





Code WL-YD2R-234P

Wattage 34W

CCT(K) 3000K/4000K/6000K

Lumen3200lmBeam Angle100°/head

Working Mode Auto/D2D/On time

Detection Brightness 5-2000Lux

Detection Range 150°,12m max

Material Po



YDR series White Black

3CCT Outdoor LED Security Light





Wide applications in various







Code WL-YDS-240P

Wattage 40W

CCT(K) 3000K/4000K/6000K

Lumen 4000lm **Beam Angle** 100°/head

Working Mode Auto/D2D/On time Detection Brightness 5-2000Lux

Detection Range 150°,10-12m max **Material** PC+Glass



YDS series white Black

3CCT Outdoor LED Security Light

























Code WL-YES-260P Wattage 60W

CCT(K) 3000K/4000K/6000K

Lumen6000lmBeam Angle100°/headWorking ModeAuto/D2D/On time

Detection Brightness5-2000LuxDetection Range150°,12m maxMaterialAL+PC





YES(R) series White Black 3CCT Round/Square LED Security Light














5CCT LED Batten Light







T8/5 series		New	
Code	SL-LT-JAL812	SL-LT-JAL512	
Wattage	10W/15W/20W	10W/14W/18W	
CCT(K)	2700K/3000K/4000K/5000K/6500K	3000K/4000K/6500K	
Lumen	2100lm max	2000lm max	
Beam Angle	120°	120°	









Code SL240WT-CCT Wattage 20W/30W/40W

CCT(K) 2700K/3000K/4000K/5000K/6000K Lumen

2400lm/3600lm/4800lm

120° **Beam Angle** Dimmable No 1.2m Length PC Material













SL series white

5CCT LED Shop Light

SL series		1 _{ex}	New
Code	SL240WT-CCT	SLC250WT-CCT	SL260-CTW
Wattage	20W/30W/40W	30W/40W/50W	40W/50W/60W
CCT(K)	2700K/3000K/4000K/5000K/6000K	3000K/4000K/5000K	2700K/3000K/4000K/5000K/6000K
Lumen	2400lm/3600lm/4800lm	3000lm/4000lm/5000lm	3600lm/4500lm/5400lm
Material	PC	PC	PC









Code SLE260-CTW Wattage 30W/45W/60W

CCT(K) 2700K/3000K/4000K/5000K/6500K

Lumen 3300lm/4400lm/5500lm

220° Beam Angle Length 1.2m PC Material














SLE series white

Omnidirectional Emitting LED Shop Light













WORK LIGHT

Code FLC36

18W/27W/36W Wattage CCT(K) 3000K/4000K/6500K

Lumen 3800lm max Input 20VDC tool battery

90°/head Beam Angle Material ABS

















FLC series (Black)

3CCT Portable LED Floodlight

















Wall Light



Cabinet Light



Solar Light





Coming Soon...









Code Wattage 3W

CCT(K) 3000K/4000K/5000K/6000K+RGB

Lumen 200lm 24° **Beam Angle Dimmable** Yes ABS **Material**

Battery 3.7V 4000mAh Type-C USB Charging **Endurance Time** 4.5h



UB01 series white

Color Changeable LED Reading Light




















CCT(K) 3000K/4000K/6000K

Lumen 320lm 0°-70° **Beam Angle** Dimmable Yes ABS Material

3.7V 4000mAh **Battery**

USB Charging Type-C **Endurance Time** 4h

Detection Range 120°, 8m max

(microwave) 20mm max (hand wave)















UB05 series white Black

3CCT Square Wall Light
































Battery

USB Charging

Endurance Time 8h

3.7V 4000mAh

Type-C




















Wireless LED Art Light












Wireless Side-Emitting Under Cabinet Bar Light

























Wireless Connectable

Convenient group control

A B C OFF

2 Beam Angles Available

Choose the one more

2 Trigger Modes

sensor activated

Motion/ Handwave

via remote control







UB02C series white

Wireless Connectable Under Cabinet Bar Light

















CCT(K) 3000K/4000K/6000K+RGB

160-180lm Lumen 45°/110° **Beam Angle Dimmable** Yes ABS Material Diameter 85mm

3.7V 2000mAh **Battery USB** Charging Type-C Endurance Time 6h





UBO6 series white

Wireless Connectable LED Cabinet Light























SPECIFICATIONS



UB | Wireless Surface-Emitting Under Cabinet Bar Light

SPECIFICATIONS				
Code	UB03-30	UB03-40	UB03-60	
Wattage	1.5W	2W	3W	
CCT(K)		3000-6500K		
Lumen	120lm	160lm	240lm	
Dimmable		Yes		
Battery 3.	7V 1500mAh 3.5	7V 2000mAh 3	3.7V 3000mAh	
USB Charging		Type-C		
Charging Time	3 hours	4 hours	5 hours	
Endurance Time		6 hours		
Working Mode	AU ⁻	TO/OFF/ON T	IME	
Detection Angle		120°		
Sensor Duration T	ime	30s		
Human Body Det	ection Distance	0-4m		
Length(L)	30cm	40cm	60cm	
Material		ABS+PC		












UB | Side-Emitting Connectable Under Cabinet Bar Light

Code	UB04-30	UB04-40	UB04-60
Wattage	5W	6.5W	10W
CCT(K)		3000K-6500K	
Lumen	400lm	520lm	800lm
Dimmable		Yes	
Input	22	0-240V~50/60	Hz
Output		24V DC	
Working Mode	AUTO/NIGH	IT/HAND WAV	E/ON TIME
Detection Angle		120°	
Sensor Duration T	ime	30s/60s/120s	
Human Body Det	ection Distance	0-4m	
Hand Scan Detec	ction Distance	<10cm	
Length(L)	30cm	40cm	60cm
Material		ABS+PC	











OT-01A-4P3 Code Wattage

3000K/4000/6500K CCT(K)

180lm Lumen 30° **Beam Angle Dimmable** Yes ABS+PC Material Height 42.6cm Solar Panel 5.5VDC **Battery** 3.7V1800mAh

USB Charging Type-C **Endurance Time** 2.5h Detection Angle 120°







Adjustable Head Illuminate specific items

you need

OT-01 series

30°/120° LED Solar Spike Light

OT series		3		3	•	3
Code	OT-01A-1D3	OT-01A-1R	OT-01A-4P3	OT-01B-1D3	OT-01B-1R	OT-01B-4P3
Wattage	2W	1.2W	4W	1.2W	1.2W	4W
Lumen	100lm	60-80lm	180lm	60-80lm	60-80lm	180lm
Illumination	240Lux/1m	240Lux/1m	750Lux/1m	240Lux/1m	240Lux/1m	750Lux
Beam Angle	30°	30°	30°	120°	120°	120°
Detection Angle	/	/	120°	/	/	120°
Endurance Time	8-10h	8-10h	2.5h	8-10h	8-10h	2.5h













PL-SR03 Code Wattage

CCT(K) 3000K/4000/6500K

75lm **Dimmable** Yes ABS+PC **Material** 5VDC **Solar Panel Battery** 3.7V 1500mAh Type-C **USB Charging Endurance Time** 12h





Wireless Connectable Convenient group control





SR/SAS series (Black)

LED Solar Patio Light

SR/SAS series	New	Non
Code	PL-SR03	PL-SAS113
Wattage	1.2W	1.6W
Lumen	75lm	1 40lm
CCT(K)	3000K/4000K/6500K	3000K/4000K/6500K
Height	620mm	755mm
Detection Range	240°,10m max	240°,10m max
Endurance Time	12h	12h

OT | Colour Adjustable LED Solar Security Light

SPECIFICATIONS OT-04 Code Wattage 5W CCT(K) 3000K-6500K Lumen 400lm max **Dimmable** Yes 100° **Beam Angle Solar Panel** 5.5VDC 3.7V 1800mAh **Charging Time** 8-10 hours by solar energy **USB** Charging 3.5 hours by Type-C 2 hours **Endurance Time** AUTO/D2D/ON TIME Worknig Mode 120° **Detection Angle** 30s/60s/120s Sensor Duration Time **Detection Distance** 9m max

ABS+PC





ССТ





IP65


OT | Colour Adjustable LED Solar Security Light

SPECIFICATIONS

Material

Code	OT-05		
Wattage 5W			
CCT(K)	3000K/4000K/6500K		
Lumen	400lm		
Dimmable	No		
Beam Angle	100°		
Solar Panel	5.5VDC		
Battery	3.7V 1800mAh		
Charging Time	8-10 hours by solar energy		
USB Charging	3.5 hours by Type-C		
Endurance Time	2 hours		
Detection Brightn	iess 5-2000Lux		
Detection Angle	120°		
Sensor Duration 1	ime 3secs-8mins		
Detection Distanc	ce 16m max		
Material	ABS+PC		

















Coming Soon...



SR260 Wall Light

- Bidirectional Lighting
 - Rotatable Head